





CLS - G 1 1

ECRAN LCD
MEDICAL


Taille



Angle vision




Luminosité




Contraste



Résolution



Weight



Modèle	CLS-G11
Panel	46 cm (18.1") TFT Monochrome
Active Display size (mm)	359 (H) x 287 (V)
Native resolution portrait	1 024 x 1 280
Native resolution landscape	1 280 x 1 024
Pixel Pitch	0.2805 x 0.2805 mm
Grayscale Tones	256 from a palette of 1.531
Viewing Angles (H / V)	+/- 85 ~ +/- 85
Brightness	700 cd/m ²
Contrast Ratio	600 : 1
Response time	40 ms
Scanning Frequency (H- V)	Analog : 27 - 82 kHz ~ 50 -85 Hz Digital : 27 - 64 kHz ~ 60 Hz
Dot Clock Analog / Digital	135 / 108 MHz
Input Signals	Analog. : RGB Analog. Digital : DVI standard 1.0
Sync. formats	Seperate, Composite, Sync-on-Green
Input Terminal	DVI-I 29 pin, BNC
USB ports	1 upstream, 2 downstream
USB standard	Standard rev.1.1
Plug and play	VESA DDC 2B
Power requirements	AC100-120V, 200-240 V : 50/60 Hz
Power Consumption	60 watts
Power save Mode	Less than 8 watts
Built-In Sensor	Backlight Sensor
Power Management	Analog. : VESA DPMS Digital : DVI DMPM
OSD languages	Anglais, Japonnais
Height Adjustment range	100 mm
Pivot	90°
Tilt / Swivel	40° Up, 0° Down / 35° Left- Right
Dimensions (W x H x D)	With stand : 399 x 404 – 504 x 202.7 mm Without stand : 399 X 328 X 65 mm
Net weight	With stand : 7.8 Kg Without stand : 5.5 Kg
Hole Spacing	VESA standard (100 x 100)
Certification and standard	CE (Medical Device Directive), TUV/GM (EN60601-1), CTUVus (UL2601-1, CSA C22.2 No. 601-1), Cb (IEC600601-1), VCCI-A, FCC-A, Canadian ICES-003-A, FDA 510(k), CCC

