




CLS - G 2 0

ECRAN LCD
MEDICAL


Taille



Angle vision




Luminosité




Contraste



Résolution



Weight



Modèle	CLS-G20
Panel	51 cm (20.1") TFT Monochrome
Active Display size (mm)	306 (H) x 408 (V)
Native resolution portrait	1 200 x 1 600
Native resolution landscape	1 600 x 1 200
Pixel Pitch	0.255 x 0.255 mm
Grayscale Tones	256 from a palette of 1.531
Viewing Angles (H / V)	+/- 85 ~ +/- 85
Brightness	700 cd/m ²
Contrast Ratio	1000 : 1
Response time	30 ms
Scanning Frequency (H- V)	31.5 - 75 kHz ~ 60 Hz
Dot Clock	162 MHz
Input Signals	DVI standard 1.0
Input Terminal	DVI-D 24 pin
USB ports	1 upstream, 2 downstream
USB standard	Standard rev.1.1
Plug and play	VESA DDC 2B
Power requirements	AC100-120V, 200-240 V : 50/60 Hz
Power Consumption	65 watts
Power save Mode	Less than 8 watts
Built-In Sensor	Backlight Sensor
Power Management	Digital : DVI DMPM
OSD languages	Anglais, Japonnais
Height Adjustment range	82 mm
Pivot	90°
Tilt / Swivel	40° Up, 0° Down / 35° Left- Right
Dimensions (W x H x D)	With stand : 347 x 497.5 – 579.5 x 208.5 mm Without stand : 347 X 449 X 86.5 mm
Net weight	With stand : 10.5 Kg Without stand : 7.3 Kg
Hole Spacing	VESA standard (100 x 100)
Certification and standard	CE (Medical Device Directive), TUV/GM (EN60601-1), CTUVus (UL2601-1, CSA C22.2 No. 601-1), Cb (IEC600601-1), VCCI-A, FCC-A, Canadian ICES-003-A, FDA 510(k), CCC

