




# CLS - G 2 2

ECRAN LCD  
MEDICAL


## Taille




## Angle vision




## Luminosité




## Contraste



## Résolution



## Weight



Modèle	CLS-G22
Panel	50 cm (19.6") TFT Monochrome
Active Display size (mm)	299 (H) x 398 (V)
Native resolution portrait	1 200 x 1 600
Native resolution landscape	1 600 x 1 200
Pixel Pitch	0.249 x 0.249 mm
Grayscale Tones	1.021 from a palette of 3.061
Viewing Angles (H / V)	+/- 85 ~ +/- 85
Brightness	800 cd/m²
Contrast Ratio	850 : 1
Response time	50 ms
Scanning Frequency (H- V)	75 KHz - 60 Hz
Dot Clock	165 MHz
Input Signals	DVI standard 1.0
Input Terminal	DVI-D 24 pin
USB ports	1 upstream, 2 downstream
USB standard	Standard rev.2.0
Plug and play	VESA DDC 2B
Power requirements	AC100-120V, 200-240 V : 50/60 Hz
Power Consumption	85 watts
Power save Mode	Less than 3 watts
Built-In Sensor	Backlight Sensor
Power Management	DVI DMPM
OSD languages	Anglais, Japonnais
Height Adjustment range	82 mm
Pivot	90°
Tilt / Swivel	40° Up, 0° Down / 35° Left- Right
Dimensions (W x H x D)	With stand : 337 x 493 – 575 x 208.5 mm Without stand : 337 X 441 X 78.5 mm
Net weight	With stand : 8.3 Kg Without stand : 5.3 Kg
Hole Spacing	VESA standard (100 x 100)
Certification and standard	CE (Medical Device Directive), TUV/GM (EN60601-1), CTUVus (UL2601-1, CSA C22.2 No. 601-1), Cb (IEC600601-1), VCCI-A, FCC-A, Canadian ICES-003-A, FDA 510(k), CCC

