




# CLS - G 3 3

ECRAN LCD  
MEDICAL


## Taille




## Angle vision




## Luminosité



## Contraste



## Résolution



## Weight



Modèle	CLS-G33
Panel	53 cm (20.8") TFT Monochrome
Active Display size (mm)	318 (H) x 424 (V)
Native resolution portrait	1 536 x 2 048
Native resolution landscape	2 048 x 1 536
Pixel Pitch	0.207 x 0.207 mm
Grayscale Tones	4.096 from a palette of 8.161
Viewing Angles (H / V)	+/- 85 ~ +/- 85
Brightness	700 cd/m <sup>2</sup>
Contrast Ratio	700 : 1
Response time	50 ms
Scanning Frequency	31 - 100 kHz, 48 - 71.5 hZ
Dot Clock	165 MHz
Input Signals	DVI standard 1.0
Input Terminal	DVI-D 24 pin
USB ports	1 upstream, 2 downstream
USB standard	Standard rev.2.0
Plug and play	VESA DDC 2B
Power requirements	AC100-120V, 200-240 V : 50/60 Hz
Power Consumption	100 watts
Power save Mode	Less than 3 watts
Built-In Sensor	Backlight Sensor
Power Management	DVI DMPM
OSD languages	Anglais, Japonnais
Height Adjustment range	82 mm
Pivot	90°
Tilt / Swivel	40° Up, 0° Down / 35° Left- Right
Dimensions (W X H X D)	With stad : 368 x 515.5 – 597.5 x 208.5 mm Without stand : 368 X 486 X 94 mm
Net weight	With stand : 10 Kg Without stand : 7 Kg
Hole Spacing	VESA standard (100 x 100)
Certification and standard	CE (Medical Device Directive), TUV/GM (EN60601-1), CTUVus (UL2601-1, CSA C22.2 No. 601-1), Cb (IEC600601-1), VCCI-A, FCC-A, Canadian ICES-003-b, FDA 510(k), CCC

