




CLS - R 2 2

ECRAN LCD
MEDICAL


Taille



Angle vision




Luminosité




Contraste



Résolution



Weight



Modèle	CLS-R22
Panel	54 cm (21.3") TFT Color
Active Display size (mm)	432 (H) x 324 (V)
Native resolution portrait	1 200 x 1 600
Native resolution landscape	1 600 x 1 200
Pixel Pitch	0.270 x 0.270 mm
Display Colors	16.77 million from a palette of 1.06 billion
Viewing Angles (H / V)	+/- 85 ~ +/- 85
Brightness	250 cd/m ²
Contrast Ratio	550 : 1
Response time	30 ms
Scanning Frequency (H- V)	Analog. : 31 - 94 kHz ~ 49 -86 Hz Digital : 31-76 kHz ~59-61 Hz
Dot Clock Analog. / Digital	202.5 / 162 MHz
Input Signals	Analog. : RGB Analog. Digital : DVI standard 1.0
Sync. Formats	Separate, Composite, Sync-on-Green
Input Terminal	D-Sub mini 15 pin, DVI-I 29 pin (switchable)
USB ports	1 upstream, 2 downstream
USB standard	Standard rev.1.1
Plug and play	VESA DDC 2B
Power requirements	AC100-120V, 200-240 V : 50/60 Hz
Power Consumption	70 watts
Power save Mode	Less than 8 watts
Built-In Sensor	Backlight Sensor
Power Management	Analog. : VESA DPMS Digital : DVI DMPM
OSD languages	Anglais, Allemand, Français, Italien Japonais
Height Adjustment range	82 mm
Pivot	90°
Tilt / Swivel	40° Up, 0° Down / 35° Left- Right
Dimensions (W x H x D)	With stand : 472 x 459 – 541 x 208.5 mm Without stand : 472 X 373 X 69 mm
Net weight	With stand : 10.2 Kg Without stand : 7 Kg
Hole Spacing	VESA standard (100 x 100)
Certification and standard	CE (Medical Device Directive), TUV/GM (EN60601-1), CTUVus (UL2601-1, CSA C22.2 No. 601-1), Cb (IEC600601-1), VCCI-A, FCC-A, Canadian ICES-003-A, FDA 510(k), CCC

